



Series 382-x

Tel: 1300 196 156 Visit: www.colourcomponents.com.au

Page 1/8

## 1 Identification of the substance/mixture and of the company/undertaking

· Product identifier

Revision: April 2012

· Trade name: Series 382 · Article number: Series 382

· Relevant identified uses of the substance or mixture and uses advised against

· Application of the substance / the preparation Printing inks

SUPPLIER: Colour Components

24 / 25 Ingleston Rd, Tingalpa QLD 4173

Tel: 1300 196 156 email: mail@colourcomponents.com.au

Emergency Information Tel: 1300 196 156

**Poisons Information Centre Hotline** 

13 11 26 (Australia)

0800 764 766 (New Zealand)

## 2 Hazards identification

· Classification of the substance or mixture

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

×

Xi; Irritant

R36: Irritating to eyes.

R10-52/53: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

· Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · Label elements
- · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xi Irritant

#### · Risk phrases:

- 10 Flammable.
- 36 Irritating to eyes.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

#### Safety phrases.

- 23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 60 This material and its container must be disposed of as hazardous waste.
- 61 Avoid release to the environment. Refer to special instructions/safety data sheets.

(Contd. on page 2)



April 2012

Page 2/8

Trade name: Series 382

· Other hazards

· Results of PBT and vPvB assessment

· **PBT:** Not applicable. · **vPvB:** Not applicable.

(Contd. of page 1)

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous compoi	nents:	
CAS: 108-65-6 EINECS: 203-603-9	2-methoxy-1-methylethyl acetate   Xi R36  R10   → Flam. Liq. 3, H226; → Eye Irrit. 2, H319	10-25%
CAS: 96-48-0 EINECS: 202-509-5	gamma-butyrolactone ■ Xn R22; ■ Xi R36 ↑ Acute Tox. 4, H302; Eye Irrit. 2, H319	10-25%
CAS: 54839-24-6 EINECS: 259-370-9	2-ethoxy-1-methylethyl acetate 2.5- R10-67 Flam. Liq. 3, H226;   STOT SE 3, H336	
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom.  Xn R20-65; N R51/53  R10-66-67  Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H332; STOT SE 3, H336	2.5-10%
CAS: 123-42-2 EINECS: 204-626-7	4-hydroxy-4-methylpentan-2-one  Xi R36  → Flam. Liq. 3, H226; → Eye Irrit. 2, H319	2.5-10%
CAS: 1333-86-4 EINECS: 215-609-9	Carbon black substance with a Community workplace exposure limit	2.5-10%
CAS: 108-94-1 EINECS: 203-631-1	cyclohexanone Xn R20 R10 → Flam. Liq. 3, H226; → Acute Tox. 4, H332	2.5-10%
CAS: 8052-41-3 EINECS: 232-489-3	Stoddard solvent  ■ Xn R65; ■ N R51/53  R10-66-67  ⑤ Flam. Liq. 3, H226; ⑥ Asp. Tox. 1, H304; ⑥ Aquatic Chronic 2, H411; ⑥ STOT SE 3, H336	< 1%
CAS: 15571-58-1 EINECS: 239-622-4	2-ethylhexyl 10-ethyl-4,4-dioctyl-7-oxo-8-oxa-3,5-dithia-4- stannatetradecanoate Xn R22-48; Xi R43 R53 ↑ Acute Tox. 4, H302; Skin Sens. 1, H317; Aquatic Chronic 4, H413	< 1%

### · Additional information:

For the wording of the listed risk phrases refer to section 16.

Note P. Benzene content in Solvent naphta < 0,1%; therefore R45 "May cause Cancer" is not necessary.

## 4 First aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.

(Contd. on page 3)



April 2012

Page 3/8

Trade name: Series 382

(Contd. of page 2)

- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed

No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Firefighting measures

- Extinguishing media
- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Specific end use(s) No further relevant information available.

GB



**April 2012** 

Page 4/8

Trade name: Series 382

(Contd. of page 3)

## 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

### 108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

Sk

### 123-42-2 4-hydroxy-4-methylpentan-2-one

WEL Short-term value: 362 mg/m³, 75 ppm Long-term value: 241 mg/m³, 50 ppm

#### 1333-86-4 Carbon black

WEL Short-term value: 7 mg/m³ Long-term value: 3.5 mg/m³

### 108-94-1 cyclohexanone

WEL Short-term value: 82 mg/m³, 20 ppm Long-term value: 41 mg/m³, 10 ppm

Sk, BMGV

- · Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

(Contd. on page 5)



**April 2012** 

Page 5/8

(Contd. of page 4)

Trade name: Series 382

· Eye protection:



Tightly sealed goggles

9 Ph	vsical	and c	hemical	pro	nerties
<i>J I II</i>	Jour	arra c	licillicai	$\rho_I \cup$	perme

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Highly viscous

Colour: According to product specification

Odour: CharacteristicOdour threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range:  $> 140 \, \text{°C}$ 

· Flash point: 44 ℃ (Abel Pensky)

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 315 ℃

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive

air/vapour mixtures are possible.

· Explosion limits:

**Lower:** 1.5 Vol % **Upper:** 15.6 Vol %

· Vapour pressure at 20 ℃: 3.4 hPa

Density: Not determined.
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· Segregation coefficient (n-octanol/water): Not determined.

Viscosity:

Dynamic at 20 ℃: 12000 mPas Kinematic: Not determined.

**VOC (EC)** 42.57 %

• Other information No further relevant information available.

GB



We're about ink and its application.

**April 2012** 

Page 6/8

Trade name: Series 382

(Contd. of page 5)

## 10 Stability and reactivity

- Reactivity
- Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:

Acute tox	icity.	
· LD/LC50 \	values rele	evant for classification:
96-48-0 ga	amma-but	yrolactone
Oral	LD50	1540 mg/kg (rat)
Dermal	LD50	5000 mg/kg (gui)
64742-95-	6 Solvent	naphtha (petroleum), light arom.
Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

(Contd. on page 7)



April 2012

Page 7/8

Trade name: Series 382

· Other adverse effects No further relevant information available.

(Contd. of page 6)

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation
- Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- European waste catalogue 08 03 12: waste ink containing dangerous substances
- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
ADR, ADN, IMDG	Void
IATA	UN1210
UN proper shipping name	
ADR, ADN, IMDG	Void
IATA	PRINTING INK
Transport hazard class(es)	
ADR	
Class	Void
	Not restricted good in accordance ADR 2.2.3.1.5
ADN/R Class:	Void
IMDG	
Class	Void
	Not restricted good in accordance to IMDG 2.3.2.5
IATA	
Class	3 Flammable liquids.
Label	3
Packing group	
ADR, IMĎG	Void
IATÁ	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.

## 15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

GB



**April 2012** 

Page 8/8

Trade name: Series 382

(Contd. of page 7)

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

### · Relevant phrases

- H226 Flammable liquid and vapour.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.
- R10 Flammable.
- R20 Harmful by inhalation.
- R22 Harmful if swallowed.
- R36 Irritating to eyes.
- R43 May cause sensitisation by skin contact.
- R48 Danger of serious damage to health by prolonged exposure.
- R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- R53 May cause long-term adverse effects in the aquatic environment.
- R65 Harmful: may cause lung damage if swallowed.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.
- · Department issuing MSDS: Product safety department
- · Contact:

Richard Gähwiler

richard.gaehwiler@printcolor.ch

C P